



Part Weight	6.58 lbs.
Min/Max Temp.	-30/140 Degrees F
Pressure Tested	4.3 PSI
Material	Flexible PVC 60 Duro Shore A
Installation Torque	60" Lbs.
Conforms to ASTM	D5926, C1173
Box Quantity	2
Clamps used	300 Series

TOLERANCES: .X= Fractional ± .XX= ±.060 .XXX= ±.032 ANG.= ±0.5° UNLESS OTHERWISE SPECIFIED	
UNITS:	SIZE
INCHES	<b>A</b>
3RD ANGLE PROJECTION DO NOT SCALE DRAWING	

DESCRIPTION: Coupling 12" Clay x 12" Ductile Iron/Asb. Cement	
<b>1003-1212</b>	
DESIGNER:	SCALE
D. Brady	not to scale
CHECKER:	DATE: 9/17/2010
	SHEET 1 OF 1

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
FERNCO, INC. ANY REPRODUCTION IN  
PART OR AS A WHOLE WITHOUT THE  
WRITTEN PERMISSION OF FERNCO, INC.  
IS PROHIBITED.